
Navis F280

CPU COOLER







Meet the Endorfy Navis F280 – an efficient AlO liquid cooling kit that can handle the requirements of even high-energy processors. Get ready for top-notch cooling performance with no fan hum. The focal point of the Endorfy Navis F280 is a pump-in-block setup with a ceramic bearing and PWM control. In addition, we'll provide you with two Fluctus fans. Thanks to their size (140 mm), they can work at a lower speed, while maintaining a level of performance that will please both you and your computer. The Endorfy Navis F280 is also compatible with all popular sockets, which allows you to install it on almost any processor. You can do that in minutes thanks to the simple mounting system and pre-installed fans.



All-in-one water cooling

High performance, preassembled water cooling loop is ready to install and maintenance-free.

PWM-controlled pump

Advanced, PWM-controlled pump is quiet at idle and efficient under load. Mounting points are integrated for hassle-free installation.

Two Fluctus fans

Fluctus fans are optimized for high static pressure, providing superb performance on water cooling radiators at low noise levels.

Extended fan speed range

Fan speed can be regulated from whisper-quiet 250 rpm up to 1800 rpm depending on cooling requirements.

Kink-resistant rubber tubing

Internally reinforced tubes are flexible and easy to route. Outer sleeves protect the tubes and provide unobtrusive looks.

Multi-socket compatibility


Redesigned mounting system is easy to install and compatible with all modern AMD and Intel desktop sockets.

Logistics data

Launch date	2022-10-05 (Wednesday)	Dimensions and weight of retail package	410×175×170 mm / 1.93 kg
Product code	EY3B002	Quantity in collection box	6 pcs
EAN	5903018665894	MSRP	98 EUR



Designed by Endoing 200-20










Technical specifications		Radiator	
Product code	EY3B002	Radiator dimensions [mm]	317×138×28
EAN	5903018665894	Radiator dimensions (incl. fans) [mm]	140 × 317 × 54
Product type	CPU liquid cooler	Material	Aluminium
Fan specifications		Pump specifications	
Fans (included)	2× Fluctus 140 PWM	Coldplate	Copper
Dimensions [mm]	140×140×25	Bearing	Ceramic
Speed [rpm]	250 (±100) –1800 (±10%)	Voltage [V]	12
Bearing	FDB	Current (peak) [A]	0.33
Control (speed)	PWM	Control (speed)	PWM
Connector	4-pin (power, male and female)	Speed [rpm]	1600 – 2600 (±10%)
Voltage [V]	12	Connector (power)	SATA
Current (fan, peak) [A]	0.3	Connector (control)	4-pin PWM (female)
MTBF[h]	100 000	Warranty [months]	36
Intel CPU compatibility		AMD CPU compatibility	
LGA 1700	Yes	AM5 / AM4	Yes
LGA 1200 / 1151 / 1150 / 1155 / 1156	Yes	AM3(+)/AM2(+)/FM2(+)/FM1	No
LGA 2066 / 2011-3 / 2011 (square ILM)	Yes		

What's in the box?







2×Fluctus 140 PWM fan (preinstalled)





Mounting accessories



Pactum PT-3 thermal compound



5 Safety instruction



ENDORFY can cater to every desire and requirement.

All you need is your imagination and passion for computer hardware. We handle the rest and deliver proven, functional and efficient products. This combination will make you proud and let you experience the emotions that come with computer hardware, its configuration and PC gaming.

